Revision: 08/06/2016

[] Industrial [X] Professional [X] Consumers



ØŠÒWÜÁÙÚÜŒŸÁWÞŒÒÜÙŒŠÁÚÜŒ ÒÜ

Code: Î HÌ Í I



Version: 2 Revision: 08/06/2016 Previous revision: 02/05/2016 Date of printing: 08/06/2016

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Code: Î HÌ Í I

RELEVANT IDENTIFIED USES AND USES ADVISED AGAINST: 1.2

Intended uses (main technical functions):

Sectors of use

Consumer uses (SU21).

Jses advised against

This product is not recommended for any use or sector of use industrial, professional or consume other than those previously listed as 'Intended or identified uses'.

Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:

Not restricted

14

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

COLORIFICIO CENTRALE S.R.L

Via Industria, 12-14-16 - 25030 Torbole Casaglia (BS) ITALY Telephone: +39 030 2151004 - Fax: +39 030 2150858 E-mail address of the person responsible for the safety data sheet:

e-mail: info@fleurpaint.com EMERGENCY TELEPHONE NUMBER: +39 030 2151004 (8:30-12:30 / 13:30 - 17:30)

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE ORMIXTURE: 21

Classification in accordance with Regulation (EC) No. 1272/2008~605/2014 (CLP)

DANGER: Flam. Aerosol 1:H222+H229 | Skin Irrit. 2:H315 | Eye Irrit. 2:H319 | STOT SE (irrit.) 3:H335 | STOT SE (narcosis) 3:H336 | STOT RE 2:H373i | **EUH066**

Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
Physicochemical: Human health:	Flam. Aerosol 1:H222+H229 Skin Irrit. 2:H315 Eye Irrit. 2:H319 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 STOT RE 2:H373i	Cat.1 Cat.2 Cat.2 Cat.3 Cat.3 Cat.2	- Skin Eyes Inhalation Inhalation Inhalation	Skin Eyes Respiratory ways CNS Systhemic	Irritation Irritation Irritation Narcosis Damage
Environment: Not classified	EUH066	-	Skin	Skin	Dryness, Cracking

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

22 LABEL FLEMENTS



This product is labelled with the signal word DANGER in accordance with Regulation (EC) No. 1272/2008~605/2014 (ČLP)

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H373i May cause damage to organs through prolonged or repeated exposure if inhaled.

H319 Causes serious eye irritation. H335 May cause respiratory irritation. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P264a Wash the hands thoroughly after handling.

P271-P260d Use only outdoors or in a well-ventilated area. Do not breathe aerosol.

P303+P361+P353-P352-P312 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of

soap and water. Call a POISON CENTER or doctor if you feel unwell.

P304+P340-P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you

feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337+P313 If eye irritation persists: Get medical attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501a Dispose of contents/container in accordance with local regulations.

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830



ØŠÒWÜÂÙÚÜŒŸÁNÞŒÒÜÙŒŠÁÚÜŒ ÒÜ

Code: Î HÌ Í I



Revision: 08/06/2016

Supplementary statements:

EUH208

Hazardous ingredients:

Xylene (mixture of isomers)

Ethyl acetate n-butyl acetate Ethylbenzene

Contains fatty acids/maleic acid aduct, 1,2-epoxypropyl p-tertbutylphenyl ether. May produce an allergic reaction.

2.3 OTHER HAZARDS

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

Other physicochemical hazards: Vapours may form with air a mixture potentially flammable or explosive. Other adverse human health effects: No other relevant adverse effects are known.

Other negative environmental effects: Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCES: 3.1

Not applicable (mixture).

3.2 **MIXTURES:**

This product is a mixture.

Chemical description:

Aerosol.

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

30 < 40 %	Dimethyl ether CAS: 115-10-6, EC: 204-065-8 CLP: Danger: Flam. Gas 1:H220 Press. Gas:H280 REACH: 01-2119472126	8-37 Index No. 603-019-00-8 < REACH
25 < 30 % (*) (*)	Xylene (mixture of isomers) CAS: 1330-20-7, EC: 215-535-7 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 Acute Tox. (skin) 4:H31 Irrit. 2:H315 Eye Irrit. 2:H319 STOT SE (irrit.) 3:H335 STOT RE 2:H373i Asp. T	2 Skin < REACH
5 < 10 %	Ethyl acetate CAS: 141-78-6, EC: 205-500-4 CLP: Danger: Flam. Liq. 2:H225 Eye Irrit. 2:H319 STOT SE (narcosis) 3:H336 I	
5 < 10 %	n-butyl acetate CAS: 123-86-4 , EC: 204-658-1 REACH: 01-211948549: CLP: Warning: Flam. Liq. 3:H226 STOTS E (na rcos is) 3:H336 EUH066	3-29 Index No. 607-025-00-1 < REACH/ATP01
1 < 3 %	Ethylbenzene CAS: 100-41-4 , EC: 202-849-4 CLP: Danger: Flam. Liq. 2:H225 Acute Tox. (inh.) 4:H332 STOT RE 2:H373iE A 1:H304 Aquatic Chronic 3:H412	
< 0,15 %	Fatty acids C14-C18 and C16-C18 unsatd CAS: 85711-46-2, EC: 288-306-2 CLP: Warning: Skin Irrit. 2:H315 Skin Sens. 1:H317 REACH: 01-2119976378	8-19 Autoclassified < REACH
< 0,15 %	1,2-epoxypropyl p-tertbutylphenyl ether CAS: 3101-60-8 , EC: 221-453-2 REACH: 01-2119959490 CLP: Warning: Skin Irrit. 2:H315 Skin Sens. 1:H317 Aquatic Chronic 2:H411	6-20 Autoclassified < REACH

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 17/12/2015.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

None

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSIST ENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfill the PBT/vPvB criteria.



ØŠÒWÜÁÙÚÜŒŸÁNÞ QXÒÜÙŒŠÁÚÜQŢ ÒÜ

Code: Î HÌ Í I



Revision: 08/06/2016

SECTION 4: FIRST AID MEASURES

4.1 4.2

DESCRIPTION OF FIRST-AID MEASURES AND MAIN SYMPTOMS AND EFFECTS, ACUTE AND DELAYED:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation:	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces irritation to mucus, coughing and breathlessness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
Skin:	Skin contact causes redness. In case of prolonged contact, the skin may become dry.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
Eyes:	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
Ingestion:	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting. Keep the patient at rest.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.

Antidotes and contraindications: Specific antidote not known.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

Extinguishing powder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Harmful. Irritant. Exposure to combustion or decomposition products may be a hazard to health.

5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or not used, combat fire from a sheltered position or at a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opossition to the wind direction.

6.2 <u>ENVIRONMENTAL PRECAUTIONS:</u>

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

6.3 <u>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:</u>

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Avoid use of solvents. Keep the remains in a closed container.

6.4 REFERENCE TO OTHER SECTIONS:

For contact information in case of emergency, see section 1.

For information on safe handling, see section 7.

For exposure controls and personal protection measures, see section 8.

For subsequent waste disposal, follow the recommendations in section 13.



ØŠÒWÜÁJÚÜŒŸÁNÞQKÒÜÙŒŠÁÚÜQŢÒÜ

Code: Î HÌ Í I



SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

Comply with the existing legislation on health and safety at work.

General recommendations:

Avoid any type of leakage or escape.

Recommendations for the prevention of fire and explosion risks:

Pressurised container. Protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not smoke.

- Flash point : -39. °C
- Autoignition temperature : # 322. °C

Upper/lower flammability or explosive limits : 2.6 - 19.9 % Volume 25°C

Recommendations for the prevention of toxicological risks:

Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. Avoid applying the product directly to people, animals, plants or foodstuffs. For exposure controls and personal protection measures, see section 8.

Recommendations for the prevention of environmental contamination:

It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. For more information, see section 10.

Class of store : According to current legislation.

Maximum storage period : 24. months

Temperature interval : min: 5. °C, max: 50. °C (recommended).

Incompatible materials:

Keep away from oxidixing agents, from strongly alkaline and strongly acid materials.

Type of packaging:

According to current legislation.

Limit quantity (Seveso III): # Directive 2012/18/EU:

Umbral inferior: 50 toneladas, Umbral superior: 200 toneladas

7.3 SPECIFIC END USES:

For the use of this product do not exist particular recommendations apart from that already indicated.



ØŠÒWÜÁÙÚÜŒŸÁMÞŒŎÜÙŒŠÁÚÜŒ ÒÜ

Code: Î HÌ Í I



Revision: 08/06/2016

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assesing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2014	<u>Year</u>	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m3	ppm	mg/m3	
Dimethyl ether		1000.	1920.	-	-	Recommended
Xylene (mixture of isomers)	1996	100.	434.	150.	651.	A4
Ethyl acetate	1996	400.	1440.	-	-	
n-butyl acetate	1998	150.	713.	200.	950.	
Ethylbenzene	2002	100.	434.	125.	543.	A3

- TLV Threshold Limit Value, TWA Time Weighted Average, STEL Short Term Exposure Limit.
- A3 Carcinogenic in animals.
- A4 Non classified as carcinogenic in humans.

BIOLOGICAL LIMIT VALUES:

Not stablished

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers: - Systemic effects, acute and chronic: Dimethyl ether - (a) 1894. (c) - (a) - (c) - (a) Xylene (mixture of isomers) 289. (a) 77.0 (c) str (a) 180. (c) - (a) Ethyl acetate 1468. (a) 734. (c) str (a) 63.0 (c) - (a) Ethylbenzene 960. (a) 480. (c) 11.0 (a) 11.0 (c) - (a) Ethylbenzene str (a) str (c) str (a) 180. (c) - (a) Ethylbenzene str (a) str (c) str (a) 180. (c) - (a) Ethylbenzene str (a) str (c) str (a) 180. (c) - (a) Ethylbenzene str (a) str (c) str (a) str (c) - (a) Tepeoxypropyl p-tertbutylphenyl ether 19.6 (a) 19.6 (c) 5.60 (a) 5.60 (c) - (a) Derived no-effect level, workers: DNEL Inhalation mg/m3 mg/cm2 mg/cm2 Dimethyl ether - (a) - (c) str (a) str st	
Dimethyl ether	, ,
Xylene (mixture of isomers) 289. (a) 77.0 (c) s/r (a) 180. (c) - (a)	
Ethyl acetate	- (c)
n-butyl acetate 960. (a) 480. (c) 11.0 (a) 11.0 (c) - (a) Ethylbenzene s/r (a) 77.0 (c) s/r (a) 180. (c) - (a)	- (c)
Ethylbenzene S/r (a) 77.0 (c) S/r (a) 180. (c) - (a)	- (c)
Fatty acids/maleic acid aduct 19.6 (a) 19.6 (c) 5.60 (a) 5.60 (c) - (a)	- (c)
19.6 (a) 19.6 (c) 5.60 (a) 5.60 (c) - (a)	- (c)
Derived no-effect level, workers: - Local effects, acute and chronic: Dimethyl ether - (a) - (c) - (a) - (a) - (a) Xylene (mixture of isomers) 289. (a) s/r (c) s/r (a) s/r (c) s/r (a) s/r (c) s/r (a) n-butyl acetate 1468. (a) 734. (c) s/r (a) s/r (c) s/r (a) s/r (c) s/r (a) Ethylbenzene 960. (a) 480. (c) s/r (a) s/r (c) s/r (a) Ethylbenzene 293. (a) s/r (c) s/r (a) s/r (c) s/r (a) Ethylacids/maleic acid aduct - (a) - (c) a/r (a) a/r (c) s/r (a) 1,2-epoxypropyl p-tertbutylphenyl ether 19.6 (a) 19.6 (c) Derived no-effect level, general population: DNEL Inhalation mg/m3 mg/kg bw/d mg/kg bw/d DNEL Cutaneous DNEL Oral mg/kg bw/d mg/kg bw/d mg/kg bw/d mg/kg bw/d	- (c)
- Local effects, acute and chronic: Dimethyl ether	- (c)
- Local effects, acute and chronic: Dimethyl ether	
Xylene (mixture of isomers) 289. (a) s/r (c) s/r (a) s/r (c) - (a)	
Ethyl acetate 1468. (a) 734. (c) s/r (a) s/r (c) b/r (a) 960. (a) 480. (c) s/r (a) s/r (c) s/r (a) s/r	- (c)
n-bútyl acetate 960. (a) 480. (c) s/r (a) s/r (c) s/r (a) s/r (c) s/r (a) Ethylbenzene 293. (a) s/r (c) s/r (a) s/r (c) s/r (a) s/r (c) - (a) Fatty acids/maleic acid aduct - (a) - (c) a/r (a) a/r (c) s/r (a) 1,2-epoxypropyl p-tertbutylphenyl ether 19.6 (a) 19.6 (c) 0.00160 (a)0.00160 (c) Derived no-effect level, general population: DNEL Inhalation mg/kg bw/d Systemic effects, acute and chronic: DNEL Oral mg/kg bw/d	- (c)
Ethylbenzene 293. (a) s/r (c) s/r (a) s/r (c) - (a) - (a	- (c)
Fatty acids/maleic acid aduct 1,2-epoxypropyl p-tertbutylphenyl ether - (a) - (c) a/r (a) a/r (c) s/r (a) 19.6 (a) 19.6 (c) 0.00160 (a)0.00160 (c) b/r (a) - (a) - (b) a/r (a) a/r (c) s/r (a) 19.6 (a) 19.6 (c) 0.00160 (a)0.00160 (c) b/r (a) - Systemic effect level, general population: - Systemic effects, acute and chronic: - Systemic effects, acute and chronic: - (a) - (b) a/r (a) a/r (c) s/r (a) - (b) DNEL Inhalation mg/kg (a) DNEL Cutaneous mg/kg bw/d mg/kg bw/d	- (c)
1,2-epoxypropyl p-tertbutylphenyl ether 19.6 (a) 19.6 (c) 0.00160 (a)0.00160 (c) b/r (a) Derived no-effect level, general population: Systemic effects, acute and chronic: DNEL Inhalation mg/m3 DNEL Cutaneous mg/kg bw/d mg/kg bw/d	- (c)
Derived no-effect level, general population: - Systemic effects, acute and chronic: DNEL Inhalation mg/m3 DNEL Cutaneous mg/kg bw/d mg/kg bw/d	- (c)
- Systemic effects, acute and chronic: mg/m3 mg/kg bw/d mg/kg bw/d mg/kg bw/d	- (c)
Dimethyl ether - (a) 471. (c) - (a) - (c) - (a)	- (c)
Xylene (mixture of isomers) 174. (a) 14.8 (c) s/r (a) 108. (c) s/r (a) 1.6	60 (c)
Ethyl acetate 734. (a) 367. (c) s/r (a) 37.0 (c) s/r (a) 4.5	50 (c)
n-butyl acetate 860. (a) 102. (c) 6.00 (a) 6.00 (c) 2.00 (a) 2.0	00 (c)
Ethylbenzene s/r (a) 15.0 (c) s/r (a) s/r (c) s/r (a) 1.6	60 (c)
Fatty acids/maleic acid aduct s/r (a) s/r (c) s/r (a) s/r (c) s/r (a) s	s/r (c)
1,2-epoxypropyl p-tertbutylphenyl ether - (a) 11.7 (c) 3.30 (a) 3.30 (c) - (a)	- (c)

- (a) Acute, short-term exposure, (c) Chronic, long-term or repeated exposure.
- (-) DNEL not available (without data of registration REACH).
- s/r DNEL not derived (not identified hazard).
- b/r DNEL not derived (low hazard).
- a/r DNEL not derived (high hazard).



ØŠÒWÜÁÙÚÜŒŸÁWÞŒÒÜÙŒŠÁÚÜŒŢÒÜ

Code: Î HÌ Í I



Revision: 08/06/2016

Derived no-effect level, general population:	DNEL Inhalation	DNEL Cutaneous	DNEL Eyes
- Local effects, acute and chronic:	mg/m3	mg/cm2	mg/cm2
Dimethyl ether	- (a) - (c)	- (a) - (c)	- (a) - (c)
Xylene (mixture of isomers)	174. (a) s/r (c)	s/r (a) s/r (c)	- (a) - (c)
Ethyl acetate	734. (a) 367. (c)	s/r (a) s/r (c)	- (a) - (c)
n-butyl acetate	860. (a) 102. (c)	s/r (a) s/r (c)	s/r (a) - (c)
Ethylbenzene	s/r (a) s/r (c)	s/r (a) s/r (c)	- (a) - (c)
Fatty acids/maleic acid aduct	- (a) - (c)	a/r (a) a/r (c)	s/r (a) - (c)
1,2-epoxypropyl p-tertbutylphenyl ether	- (a) 11.7 (c)	0.000950 (a)0.000950 (c)	b/r (a) - (c)

- (a) Acute, short-term exposure, (c) Chronic, long-term or repeated exposure.
- (-) DNEL not available (without data of registration REACH).
- s/r DNEL not derived (not identified hazard).
- b/r DNEL not derived (low hazard).
- a/r DNEL not derived (high hazard).

PREDICTED NO-EFFECT CONCENTRATION (PNEC):

Predicted no-effect concentration, aquatic organisms: - Fresh water, marine water and intermitent release: Dimethyl ether Xylene (mixture of isomers) Ethyl acetate n-butyl acetate Ethylbenzene Fatty acids/maleic acid aduct 1,2-epoxypropyl p-tertbutylphenyl ether	PNEC Fresh water mg/l 0.155 0.327 0.260 0.180 0.100 s/r 0.00750	PNEC Marine mg/l 0.0160 0.327 0.0260 0.0180 0.0100 - 0.000750	PNEC Intermittent mg/l 1.55 0.327 1.65 0.360 0.100 s/r 0.0750
- Wastewater treatment plants (STP) and sediments in fresh- and marine water: Dimethyl ether Xylene (mixture of isomers) Ethyl acetate n-butyl acetate Ethylbenzene Fatty acids/maleic acid aduct 1,2-epoxypropyl p-tertbutylphenyl ether	PNEC STP mg/l 160. 6.58 650. 35.6 9.60 s/r 100.	PNEC Sediments mg/kg dry weight 0.681 12.5 1.25 0.981 13.7 s/r 33.5	PNEC Sediments mg/kg dry weight 0.0690 12.5 0.125 0.0981 1.37 s/r 3.35
Predicted no-effect concentration, terrestrial organisms: - Air, soil and effects for predators and humans: Dimethyl ether Xylene (mixture of isomers) Ethyl acetate n-butyl acetate Ethylbenzene Fatty acids/maleic acid aduct 1,2-epoxypropyl p-tertbutylphenyl ether	PNEC Air mg/m3 s/r - s/r	PNEC Soil mg/kg dry weight 0.0450 2.31 0.240 0.0903 2.68 s/r 11.4	PNEC Oral mg/kg bw/d 200. n/b 20.0 n/b

- (-) PNEC not available (without data of registration REACH).
- s/r PNEC not derived (not identified hazard).
- n/b PNEC not derived (not bioaccumulative potential).

8.2 EXPOSURE CONTROLS:

ENGINEERING MEASURES:





Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

<u>Protection of respiratory system:</u> Avoid the inhalation of vapours.

Protection of eyes and face: It is recommended to dispose of water taps or sources with clean water close to the working area.

Protection of hands and skin: It is recommended to dispose of water taps or sources with clean water close to the working area. Barrier creams may help

to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCUPATIONAL EXPOSURE CONTROLS: Directive 89/686/EEC~96/58/EC:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding EC marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:	Suitable combined filter mask for gases, vapours and particles (EN14387/EN143). Classe 1: low capacity up to 1000 ppm, Classe 2: medium capacity up to 5000 ppm, Classe 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume.
Goggles:	Safety goggles with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	No.

MATERIAL SAFETY DATA SHEET (REACH)

ordand	ce with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830	
F	leur	ØŠÒMÜÂÙÚÜŒŸÁMÞŒÒÜÙŒŠÁÚÜŒ ÒÜ Code:ÎHÌÍI	
G	loves:	Gloves resistant against chemicals (EN374). There are several factors (for example, temperature), they do of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN37 variety of circumstances and possibilities, we must have in mind the manual of instructions from manufacture the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the proper technique of immediately replaced when any sign of degradation is noted.	74. Due to the wide ers of gloves. Use
<u>B</u>	oots:	No.	
A	pron:	No.	

Revision: 08/06/2016

Relative water

Page 7/12

Thermal hazards:

Clothina:

Not applicable (the product is handled at room temperature).

Advisable.

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

Spills in water: Do not allow to escape into drains, sewers or water courses.

Water Control Act: # Este producto contiene las siguientes sustancias incluidas en la lista de sustancias prioritarias en el ámbito de la política de aguas, según la Directiva 2000/60/CE~2013/39/UE: Triclorometano (cloroformo).

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. When possible, avoid solvent release to the atmosphere; do not pulverize more than is strictly necessary.

VOC (industrial installations): # Si el producto se utiliza en una instalación industrial, se debe verificar si es de aplicación la Directiva 2010/75/UE (RD.815/2013), relativa a la limitación de emisiones de compuestos orgánicos volátiles debidas al uso de disolventes orgánicos en determinadas actividades industriales: Disolventes: 85.2% Peso, COV (suministro): 85.1% Peso, COV: 56.7% C (expresado como carbono), Peso molecular (medio): 77.3, Número atomos C (medio): 4.3.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Q 1	INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Appearance

Physical state Aerosol. Characteristic Odour

Odour threshold Not available (mixture).

pH-value

Not applicable Hq -Change of state

Not applicable (mixture). Melting point

 Initial boiling point Not applicable Density.

0.826 at 20/4°C Stability

- Decomposition temperature Not available Viscosity:

Viscosity (flow time) Not applicable Volatility:

- Vapour pressure Not available Solubility(ies)

- Solubility in water: Not miscible Solubility in oils and fats: Not applicable Flammability:

Flash point

-39. °C 2.6 - 19.9 % Volume 25°C 322. °C Upper/lower flammability or explosive limits Autoignition temperature

Explosive properties

- Relative density

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

Oxidizing propertie

Not classified as oxidizing product.

OTHER INFORMATION: 9.2

- Heat of combustion 7803. Kcal/kg % Weight Solids 14.7 85.1 % Weight

VOC (supply) - VOC (supply) 702.8 a/l

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the technical data sheet of the same. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY:

Corrosivity to metals: It is not corrosive to metals. Pyrophorical properties: It is not pyrophoric.

10.2 CHEMICAL STABILITY:

Stable under recommended storage and handling conditions.

Revision: 08/06/2016

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

	a (2	=0) . to:			
1	Fleur	ØŠÒWÜÁÙÚÜŒŸÁVÞŒÒN Code:ÎHÌÍI	ÜÙŒŠÁÚÜŒÒÜ		
10.3		ZARDOUS REACTIONS: reaction with oxidizing agents,	acids, alkalis, amines, pero	oxides.	
10.4	CONDITIONS TO AVC - Heat: Keep away fin - Light: Avoid direct c - Air: Not applicable. - Humidity: Avoid ext - Pressure: Not applica - Shock: Not applica	om sources of heat. contact with sunlight. treme humidity conditions. cable.			
10.5	INCOMPATIBLE MATI	ERIALS: ixing agents, from strongly alka	aline and strongly acid mat	erials.	
10.6		MPOSITION PRODUCTS: permal decomposition, hazard	ous products may be produ	uced: carbon monoxide.	

SECTION 11: TOXIC OLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EC) No. 1272/2008~605/2014 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations	DL50 (OECD 401)	DL50 (OECD 402)	CL50 (OECD 403)
for individual ingredients :	mg/kg oral	mg/kg cutaneous	mg/m3.4h inhalation
Dimethyl ether			> 100000 Rat
Xylene (mixture of isomers)	4300. Rat	1700. Rabbit	> 22080. Rat
Ethyl acetate	5620. Rat	18000. Rabbit	> 44000. Rat
n-butyl acetate	10768. Rat	17600. Rabbit	> 23400. Rat
Ethylbenzene	3500. Rat	15400. Rabbit	> 17400. Rat
Fatty acids/maleic acid aduct	> 2000. Rat		
1,2-epoxypropyl p-tertbutylphenyl ether	> 2000. Rat	> 2000. Rat	

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EX POS URE: Acute toxicity:

IN ONLINE THOUSE OF EXTOOPED OF EXTOOPED TO AND TO						
Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed			
Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).			
Skin: Not classified	ATE > 2000 mg/kg	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).			
Eyes: Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).			
Ingestion: Not classified	ATE > 5000 mg/kg	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).			

CORROSION/IRRITATION/SENSITISATION:

CORROSION/IRRITATION/SENSITISATION.						
Danger class	Target organs	Cat.	Main effects, acute and/or delayed			
Respiratory corrosion/irritation:	Respiratory ways	Cat.3	IRRITANT: May cause respiratory irritation.			
Skin corrosion/irritation:	Skin	Cat.2	IRRITANT: Causes skin irritation.			
Serious eye damage/irritation:	Eyes	Cat.2	IRRITANT: Causes serious eye irritation.			
Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).			
Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).			

^{· |} Contains fatty acids/maleic acid aduct, 1,2-epoxypropyl p-tertbutylphenyl ether. May produce an allergic reaction.



ØŠÒWÜÁÙÚÜŒŸÁWÞŒKÒÜÙŒŠÁÚÜŒ ÒÜ

Code: Î HÌ Í I



Revision: 08/06/2016

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed			
Aspiration hazard: Not classified	-	-	Not applicable.			

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Targetorgans	Cat.	Main effects, acute and/or delayed
Systhemic:	RE	Systhemic	Cat.2	# HARMFUL: May cause damage to organs through prolonged or repeated exposure if inhaled.
Cutaneous:	RE	Skin	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.
Neurological:	SE	CNS	Cat.3	NARCOTIC: May cause drowsiness or dizziness if inhaled.

CMR EFFECTS:

Carcinogenic effects: Is not considered as a carcinogenic product.

Genotoxicity: Is not considered as a mutagenic product.

Toxicity for reproduction: Do not harm fertility. Do not harm the fetus developping.

Effects via lactation: Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: Harmful by inhalation. Harmful in contact with skin. Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. Irritating to skin. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours.

Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINE TICS, METABOLISMAND DISTRIBUTION:

Dermal absorption: Not available.

Basic toxicokinetics: Not available.

ADDITIONAL INFORMATION:

Not available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EC) No. 1272/2008~605/2014 (CLP).

TOXICITY:

Acute toxicity in aquatic environment for individual ingredients: Dimethyl ether Xylene (mixture of isomers) Ethyl acetate n-butyl acetate Ethylbenzene Fatty acids/maleic acid aduct	CL50 (OECD 203) mg/l.96hours 4100. Fishes 14. Fishes 212. Fishes 18. Fishes 12. Fishes	CE50 (OECD 202) mg/l.48hours 4400. Daphnia 16. Daphnia 164. Daphnia 44. Daphnia 1.8 Daphnia > 100. Daphnia	CE50 (OECD 201) mg/l.72hours > 10. Algae > 100. Algae 675. Algae 33. Algae > 100. Algae
1,2-epoxypropyl p-tertbutylphenyl ether	7.5 Fishes	68. Daphnia	9.0 Algae
No observed effect concentration	NOEC (OECD 210) mg/l.28days	NOEC (OECD 211) mg/l.21days	
n-butyl acetate	3,	23. Daphnia	

Lowest observed effect concentration

Not available

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

ØŠÒWÜÂÙÚÜŒŸÁNÞŒÒÜÙŒŠÁÚÜŒ ÒÜ

Code: Î HÌ Í I



122	PERSISTENCE AND DEGRADABILITY:
12.2	I FERSIS I ENGE AND DEGRADADILITI.

Not available.

<u>Aerobic biodegradation</u>	DQO	%DBO/DQO	Biodegradability
for individual ingredients :	mgO2/g	5 days 14 days 28 days	
Dimethyl ether	1041.	~ 1. ~ 3. ~ 5.	Not easy
Xylene (mixture of isomers)	2620.	~ 52. ~ 81. ~ 88.	Easy
Ethyl acetate	1540.	~ 62. ~ 69. ~ 94.	Easy
n-butyl acetate	2204.	~ 80. ~ 82. ~ 83.	Easy
Ethylbenzene	3164.	~ 30. ~ 68. ~ 79.	Easy
Fatty acids/maleic acid aduct		20. 32. 35.	Noteasy
1,2-epoxypropyl p-tertbutylphenyl ether		1.	Noteasy

12.3 BIOACCUMULATIVE POTENTIAL:

Not available.

Bioaccumulation	logPow	BCF		<u>Potential</u>
for individual ingredients :	0.0700	L/kg	(aglaulated)	Liplikoly low
Dimethyl ether Xylene (mixture of isomers)	0.0700 3.16	57.	(calculated) (calculated)	Unlikely, low
Ethyl acetate	0.730	3.2	(calculated)	No bioaccumulable
n-butyl acetate	1.81	6.9	(calculated)	No bioaccumulable
Ethylbenzene	3.15	56.	(calculated)	Low
Fatty acids/maleic acid aduct				No bioaccumulable
1,2-epoxypropyl p-tertbutylphenyl ether	3.59	98.	(calculated)	Low

12.4 MOBILITY IN SOIL:

Not available.

12.5 RESULTS OF PBT AND VPVB ASSESMENT: Annex XIII of Regulation (EC) no. 1907/2006:

Does not contain substances that fulfill the PBT/vPvB criteria.

12.6 OTHER ADVERSE EFFECTS:

Ozone depletion potential: Not available.

Photochemical ozone creation potential: Not available.

Earth global warming potential: In case of fire or incineration liberates CO2.

Endocrine disrupting potential: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS: # Directive 2008/98/EC~Regulation (EU) no. 1357/2014:

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: # Directive 94/62/EC~2005/20/EC, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed of in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification,)in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself. Ensure the container is completely empty before throwing it away.

Procedures for neutralising or destroying the product:

In accordance with local regulations. Do not incinerarate closed containers.



ØŠÒWÜÁÙÚÜŒŸÁNÞ QXÒÜÙŒŠÁÚÜŒŢ ÒÜ

Code: Î HÌ Í I



Revision: 08/06/2016

SECTION 14: TRANSPORT INFORMATION

14.1 <u>UN NUMBER:</u> 1950

14.2 <u>UN PROPER SHIPPING NAME:</u>

AEROSOLS

14.3 TRANSPORT HAZARD CLASS(ES) AND PACKING GROUP:

14.4

<u>Transport by road (ADR 2015) and</u> <u>Transport by rail (RID 2015):</u>

- Class: 2
- Packaging group: - Classification code: 5F
- Tunnel restriction code: (D)

- Transport category: 2, max. ADR 1.1.3.6. 333 L

- Limited quantities: LQ2 (see total exemptions ADR 3.4)

- Transport document: Consignment paper.

- Instructions in writing: ADR 5.4.3.4

Transport by sea (IMDG 37-14):

- Class: 2
- Packaging group: - Emergency Sheet (EmS): F-D,S-U
- First Aid Guide (MFAG): 620*
- Marine pollutant: No.

- Transport document: Shipping Bill of lading.

Transport by air (ICAO/IATA 2015):

- Class: 2

- Packaging group: -

- Transport document: Air Bill of lading.

Transport by inland waterways (ADN):

Not available.

14.5 **ENVIRONMENTAL HAZARDS**:

Not applicable (not classified as hazardous for the environment).

14.6 SPECIAL PRECAUTIONS FOR USER:

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are in a vertical position and sure. Ensure adequate ventilation.

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1 EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:

The regulations applicable to this product generally are listed throughout this material safety data sheet.

Restrictions on manufacture, placing on market and use: See section 1.2

Control of the risks inherent in major accidents (Seveso III): See section 7.2

Tactile warning of danger: If the product is intended for the general public, is mandatory a tactile warning of danger. The technical specifications for tactile warning devices shall conform with EN ISO standard 11683 relating to 'Packaging - Tactile warnings of danger - Requirements.'

Child safety protection: Not applicable (the classification criteria are not met).

Legislación específica sobre aerosoles:

It is applicable the Directive 75/324/EEC~2013/10/EU, relating to aerosol dispensers and the Directive 87/404/EEC, concerning simple preasure packages.

OTHER REGULATIONS:

Not available

15.2 CHEMICAL SAFETY ASSESSMENT:

For this mixture has not been carried out a chemical safety assessment.

MATERIAL SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830



ØŠÒWÜÁÙÚÜŒŸÁWÞŒÒÜÙŒŠÁÚÜŒŢÒÜ

Code: Î HÌ Í I



Page 12 / 12

Revision: 08/06/2016

SECTION 16: OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EC) No. 1272/2008~605/2014 (CLP), Annex III:

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure: may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H373i May cause damage to organs through prolonged or repeated exposure if inhaled. H373iE May cause damage to hearing organs through prolonged or repeated exposure if inhaled.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of material safety data sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- · European Chemicals Agency: ECHA, http://echa.europa.eu/
- · Access to European Union Law, http://eur-lex.europa.eu/
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- · Threshold Limit Values, (AGCIH, 2014).
- · European agreement on the international carriage of dangerous goods by road, (ADR 2015).
- International Maritime Dangerous Goods Code IMDG including Amendment 37-14 (IMO, 2014).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this material safety data sheet:

- · REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- · DSD: Dangerous Substances Directive.
- · DPD: Dangerous Preparations Directive.
- · GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- · CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- · EINECS: European Inventory of Existing Commercial Chemical Substances.
- · ELINCS: European List of Notified Chemical Substances.
- · CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- · UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials).
- · SVHC: Substances of Very High Concern.
- · PBT: Persistent, bioaccumulable and toxic substances.
- · vPvB: Very persistent and very bioaccumulable substances.
- · VOC: Volatile Organic Compounds.
- · DNEL: Derived No-Effect Level (REACH).
- · PNEC: Predicted No-Effect Concentration (REACH).
- · LD50: Letal dose, 50 percent.
- · LC50: Letal concentration, 50 percent.
- UN: United Nations Organisation.
- · ADR: European agreement concerning the international carriage of dangeous goods by road.
- · RID: Regulations concerning the international transport of dangeous goods by rail.
- · IMDG: International Maritime code for Dangerous Goods.
- · IATA: International Air Transport Association.
- · ICAO: International Civil Aviation Organization.

MATERIAL SAFETY DATA SHEET REGULATIONS:

Material Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

 HISTORY:
 Revision:

 Version:
 1
 02/05/2016

 Version:
 2
 08/06/2016

Modifications with respect to the previous Material Safety Data Sheet:

The possible legislative, contextual, numerical, methodological and normative changes with respect to the previous version are highlighted in this Material Safety Data Sheet by a mark # in red and italic.

The information of this Material Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.