



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 1/17
Replaced revision:11 (Dated: 03/04/2020)

SAFETY DATA SHEET

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: Various
Product name: Lime Paint Base Coat

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Water-based paint for walls.

Uses Advised Against

Uses other than those identified as relevant in the previous point.

1.3. Details of the supplier of the safety data sheet

Name
Full address: COLORIFICIO CENTRALE S.R.L.
District and Country: Via Industria 12,14,16
25030 Torbole Casaglia, Brescia (BS) - IT

e-mail address of the competent person: info@fleurpaint.com
responsible for the Safety Data Sheet
Product distribution by:

1.4. Emergency telephone number

For urgent inquiries refer to
ITALY MILANO: CAV Ospedale Niguarda Ca' Granda +39 0266101029
-
United Kingdom: National Poisons Information Service - City Hospital, Birmingham
B187QH, United Kingdom +44 121 507 4123
-
Ireland: National Poisons Information Centre - Beaumont Hospital, Beaumont, Dublin
9.,
Ireland +35318092566
-
Malta: Malta Competition and Consumer Affairs Authority (MCCAA) Mizzi House,
National Road, Blata I-Bajda HMR9010, Malta +356 2395 2000
Malta: Mater Dey Hospital: Tel: 2545 0000

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 2/17
Replaced revision:11 (Dated: 03/04/2020)

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3

H412

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains: Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one
May produce an allergic reaction.

Precautionary statements:

P501 Dispose of the product / container in accordance with local / regional / national / international regulations.
P273 Avoid release to the environment.

VOC (Directive 2004/42/EC) :

Coatings for exterior walls of mineral substrate.

VOC given in g/litre of product in a ready-to-use condition : 10,00

Limit value: 40,00

This paint contains a biocidal product for the preservation of masonry works, by controlling microbiological and algal attacks.
Active ingredients: 2-octyl-2H-isothiazol-3-one, Pyrithione zinc, Terbutryn.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
TITANIUM DIOXIDE		
CAS 13463-67-7	$5 \leq x < 6$	
EC 236-675-5		
INDEX -		
Reg. no. 01-2119489379-17-0021		



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 3/17
Replaced revision:11 (Dated: 03/04/2020)

PALYGORSKITE

CAS 12174-11-7 $1 \leq x < 1,5$

EC

INDEX -

1,2-benzisothiazol-3(2H)-one

CAS 2634-33-5 $0,0224 \leq x < 0,0234$ Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC 220-120-9

INDEX 613-088-00-6

Reg. no. 01-2120761540-60

Pyrrithione zinc

CAS 13463-41-7 $0,02 \leq x < 0,021$ Acute Tox. 2 H330, Acute Tox. 3 H301, Eye Dam. 1 H318, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10

EC 236-671-3

INDEX -

Reg. no. Esente (biocida)

Terbutryn

CAS 886-50-0 $0,0031 \leq x < 0,0041$ Acute Tox. 4 H302, Skin Sens. 1B H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100

EC 212-950-5

INDEX -

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one

CAS 55965-84-9 $0,0015 \leq x < 0,0016$ Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071

EC 611-341-5

INDEX 613-167-00-5

Reg. no. 01-2120764691-48

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Information not available

4.3. Indication of any immediate medical attention and special treatment needed

Information not available



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 4/17
Replaced revision:11 (Dated: 03/04/2020)

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10.

Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 5/17
Replaced revision:11 (Dated: 03/04/2020)

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
SVK	Slovensko	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov
	TLV-ACGIH	ACGIH 2019

TITANIUM DIOXIDE Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
VLA	ESP	10				
VLEP	FRA	10				
WEL	GBR	4				RESP
WEL	GBR	10				INHAL
TLV	GRC		10			
NDS/NDSch	POL	10				INHAL
NPEL	SVK	5				
TLV-ACGIH		10				
Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,184	mg/l	
Normal value in marine water				0,018	mg/l	
Normal value for fresh water sediment				1000	mg/kg/d	
Normal value for marine water sediment				100	mg/kg/d	
Normal value for water, intermittent release				0,193	mg/l	
Normal value of STP microorganisms				100	mg/l	
Normal value for the terrestrial compartment				100	mg/kg/d	

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers			Effects on workers		
----------------------	--	--	--------------------	--	--



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 6/17
Replaced revision:11 (Dated: 03/04/2020)

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				700 mg/kg bw/d				
Inhalation							10 mg/m3	

1,2-benzisothiazol-3(2H)-one

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00403	mg/l
Normal value in marine water	0,000403	mg/l
Normal value for fresh water sediment	0,0499	mg/kg/d
Normal value for marine water sediment	0,00499	mg/kg/d
Normal value for water, intermittent release	0,0011	mg/l
Normal value of STP microorganisms	1,03	mg/l
Normal value for the terrestrial compartment	3	mg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		NPI				
Inhalation	NPI	NPI	NPI	1,2 mg/m3	NPI	NPI	NPI	6,81 mg/m3
Skin		NPI		0,345 mg/kg bw/d		NPI		0,966 mg/kg bw/d

Pyrrithione zinc

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00009	mg/l
Normal value in marine water	0,00009	mg/l
Normal value for fresh water sediment	0,0095	mg/kg/d
Normal value for marine water sediment	0,0095	mg/kg/d
Normal value of STP microorganisms	0,01	mg/l
Normal value for the food chain (secondary poisoning)	NPI	
Normal value for the terrestrial compartment	1,02	mg/kg/d
Normal value for the atmosphere	VND	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Skin				0,01 mg/kg bw/d				

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00339	mg/l
Normal value in marine water	0,00339	mg/l
Normal value for fresh water sediment	0,027	mg/kg/d
Normal value for marine water sediment	0,027	mg/kg/d
Normal value for water, intermittent release	0,00339	mg/l
Normal value of STP microorganisms	0,23	mg/l



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 7/17
Replaced revision:11 (Dated: 03/04/2020)

Normal value for the food chain (secondary poisoning)				NPI				
Normal value for the terrestrial compartment				0,01		mg/kg/d		
Normal value for the atmosphere				VND				
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,11 mg/kg bw/d		0,09 mg/kg bw/d				
Inhalation	0,04 mg/m3	NPI	0,02 mg/m3	NPI	0,04 mg/m3	NPI	0,02 mg/m3	NPI
Skin	VND	NPI	NPI	NPI	VND	NPI	NPI	NPI

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 8/17
Replaced revision:11 (Dated: 03/04/2020)

9.1. Information on basic physical and chemical properties

Appearance	viscous liquid	
Colour	Various (see section 16)	
Odour	Slight smell of water-based paint	
Odour threshold	Not available	Reason for missing data:Mild odor. No olfactory threshold available for the substances contained in the mixture.
pH	8,5	
Melting point / freezing point	0 °C	
Initial boiling point	100 °C	Reason for missing data:Mixture, technically not possible. 100 ° C the component with the lower boiling point.
Boiling range	Not determined	Reason for missing data:Mixture, technically not possible.
Flash point	> 61 °C	
Evaporation Rate	Not determined	
Flammability of solids and gases	not applicable	Reason for missing data:the mixture is liquid
Lower inflammability limit	Not applicable	Reason for missing data:the mixture is not flammable
Upper inflammability limit	Not applicable	Reason for missing data:the mixture is not flammable
Lower explosive limit	Not applicable	Reason for missing data:the mixture is not explosive
Upper explosive limit	Not applicable	Reason for missing data:the mixture is not explosive
Vapour pressure	17,5 mmHg	Substance:WATER
Vapour density	1	Substance:WATER
Relative density	1,37± 0,05 kg/l kg/l	
Solubility	Partially miscible in water	
Partition coefficient: n-octanol/water	Not applicable	Reason for missing data:Mixture, technically not possible.
Auto-ignition temperature	Not applicable	Reason for missing data:the mixture is not flammable
Decomposition temperature	Not applicable	Reason for missing data:Mixture not subject to decomposition
Viscosity	6400 - 9600 cP	Method:Dynamic viscosity
Explosive properties	Not explosive	
Oxidising properties	Non oxidizing	

9.2. Other information

Total solids (250°C / 482°F)	58,47 %
VOC (Directive 2004/42/EC) :	0,40 % - 5,45 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 9/17
Replaced revision:11 (Dated: 03/04/2020)

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

1,2-benzisothiazol-3(2H)-one



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 10/17
Replaced revision:11 (Dated: 03/04/2020)

LD50 (Oral) 490 mg/kg rats

LD50 (Dermal) > 2000 mg/kg rats

TITANIUM DIOXIDE

LD50 (Oral) > 5000 mg/kg Rat

LD50 (Dermal) 2000 mg/kg Metodo di calcolo

LC50 (Inhalation) 3,43 mg/l/4h Ratto

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one

LD50 (Oral) > 5000 mg/kg calcolato

LD50 (Dermal) > 5000 mg/kg calcolato

LC50 (Inhalation) > 5 mg/l/4h Calcolato

Pyrrithione zinc

LD50 (Oral) 221 mg/kg ratto

LD50 (Dermal) > 2000 mg/kg ratto

LC50 (Inhalation) 0,84 mg/l/4h Ratto

Natural calcium carbonate

LD50 (Oral) > 5000 mg/kg ratto

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction. Contains: Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one
1,2-benzisothiazol-3(2H)-one

GERM CELL MUTAGENICITY



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 11/17
Replaced revision:11 (Dated: 03/04/2020)

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

PALYGORSKITE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC), if the fibres are longer than 5 microns. REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

1,2-benzisothiazol-3(2H)-one

LC50 - for Fish

1,6 mg/l/96h Oncorhynchus mykiss (OECD 203)

EC50 - for Crustacea

3,27 mg/l/48h Daphnia magna (OECD 202)

EC50 - for Algae / Aquatic Plants

0,11 mg/l/72h Selenastrum capricornutum (OECD201)

EC10 for Algae / Aquatic Plants

0,0403 mg/l/72h Selenastrum capricornutum (OECD201)

Chronic NOEC for Fish

0,21 mg/l Oncorhynchus mykiss (OECD 215)

Chronic NOEC for Crustacea

1,2 mg/l Daphnia Magna (OECD 211)

Chronic NOEC for Algae / Aquatic Plants

0,0403 mg/l

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one

LC50 - for Fish

0,22 mg/l/96h Pesce - Oncorhynchus mykiss

EC50 - for Crustacea

0,1 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

0,0052 mg/l/72h Skeletonema costatum RAC

Chronic NOEC for Fish

0,098 mg/l 28 d oncorhynchus mykiss

Chronic NOEC for Crustacea

0,004 mg/l 21d Daphnia Magna

Chronic NOEC for Algae / Aquatic Plants

0,00064 mg/l 48h Skeletonema costatum rac



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 12/17
Replaced revision:11 (Dated: 03/04/2020)

Terbutryn
EC50 - for Algae / Aquatic Plants 0,0067 mg/l/72h *scenedesmus subspicatus*

Pyrithione zinc
LC50 - for Fish 0,0104 mg/l/96h *Brachydanio rerio*
EC50 - for Crustacea 0,051 mg/l/48h *Daphnia magna*
EC50 - for Algae / Aquatic Plants 0,0013 mg/l/72h *Skeletonema costatum*
Chronic NOEC for Fish 0,00125 mg/l *Brachydanio rerio*
Chronic NOEC for Crustacea 0,0022 mg/l 28 days
Chronic NOEC for Algae / Aquatic Plants 0,00046 mg/l *Skeletonema costatum*

Natural calcium carbonate
LC50 - for Fish > 10000 mg/l/96h *Trota Iridea*
EC50 - for Crustacea > 1000 mg/l/48h *Daphnia magna*
EC50 - for Algae / Aquatic Plants > 200 mg/l/72h *alga verde*

12.2. Persistence and degradability

1,2-benzisothiazol-3(2H)-one
Solubility in water 1,288 mg/l
Rapidly degradable
OECD 302 B Zahn-Wellens Test 90% (fanghi attivi)

TITANIUM DIOXIDE
Solubility in water < 0,001 mg/l
Degradability: information not available

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one
Entirely degradable

Biodegradabile in impianti di fanghi attivi

Terbutryn
Solubility in water 25 mg/l
NOT rapidly degradable

Pyrithione zinc
Rapidly degradable
OECD 302 B Zahn-Wellens Test 90% (fanghi attivi)

Natural calcium carbonate
Degradability: information not available



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 13/17
Replaced revision:11 (Dated: 03/04/2020)

Non Applicabile

12.3. Bioaccumulative potential

1,2-benzisothiazol-3(2H)-one

Partition coefficient: n-octanol/water

0,7 Log Kow OECD 117

BCF

6,95 - Pesce (OECD 305)

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one

Partition coefficient: n-octanol/water

< 0,71 Log Kow

BCF

3,16 - Calculated

Terbutryn

Partition coefficient: n-octanol/water

3,2

BCF

103 Calculated

Pyriithione zinc

Partition coefficient: n-octanol/water

1,21 Log Kow

BCF

1,4 -

Natural calcium carbonate

Partition coefficient: n-octanol/water

< 1 stimato

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 14/17
Replaced revision:11 (Dated: 03/04/2020)

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 15/17
Replaced revision:11 (Dated: 03/04/2020)

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point

3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

Coatings for exterior walls of mineral substrate.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 16/17
Replaced revision:11 (Dated: 03/04/2020)

Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament



FLEUR DESIGNER'S PAINT

LIME PAINT BASE COAT

Revision nr. 12
Dated 21/05/2020
Printed on 03/11/2020
Page n. 17/17
Replaced revision:11 (Dated: 03/04/2020)

6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

REGULATION (EU) n. 528/2012 OF THE EUROPEAN PARLIAMENT (BPR)

The following sheet is valid for colors made with the formulations in the tintometric system based on the study carried out in support.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09.