



Blanchon
Quality is in our nature

Blanchon PAINT REMOVER – DECAPANT 10'

A result of the new "high power" technology, the DÉCAPANT BÂTIMENT 10' GÉLIFIÉ BLANCHON paint remover, represents a real alternative to chlorinated removers where it has nothing to do with common ones. Its effective and fast action (10 minutes, in one application), was developed to facilitate application on vertical surfaces.

The paint remover DÉCAPANT BÂTIMENT 10' GÉLIFIÉ removes paints, varnishes, impregnation varnishes, solvents and acrylics, and can be used on all surfaces: wood, metal, glass, concrete, etc. (Except for plastics, where a preliminary test is recommended in an inconspicuous area).

1**STEP**

PREPARATION

- For all surfaces (on thin surfaces and plastics, a test should be carried out on an inconspicuous area before initial application).
- On very glossy surfaces (or a very smooth coating), it is recommended that before applying the corrosive DÉCAPANT BÂTIMENT 10' GÉLIFIÉ, it is recommended to rub it lightly with a sandpaper to facilitate corrosion.

NB: Its composition, a very strong gel form, (neutral pH, without acid or NMP) gives it the ability to be used on wood without blackening it and on ferrous metals without altering them.

2**STEP**

APPLICATION

- Ready to use. Shake well before use.
- Open the plastic lid carefully.
- To be applied in well-ventilated areas. Wear protective goggles and gloves. Do not apply in direct sunlight.
- Do not leave plants and aquariums in contact with product vapors.
- Apply a coat of DÉCAPANT BÂTIMENT 10' GÉLIFIÉ corrosive with an old brush.
- Leave for 10 minutes to act so that the coating to be removed is puffed up and can be removed from the substrate.
- Scrape off any debris without injuring the surface (use a spatula or fine wire).
- On extremely durable materials, apply a 2nd coat.
- Rinse with water to achieve a clean surface (water pressure is recommended), free of any dry residue.
- After drying the surface, rub lightly with a thin sandpaper.
- Apply the new finish.



TECHNICAL FEATURES

COMPOSITION	Selected solvents, acid-free and NMP
DENSITY (at 20°C)	0,85
FORM	Gel
DRYING TIMES (at 20°C)	Between Layers : 6 Hours Dry: 24 hours In use : 72 hours
YIELD	4-5m ² /L (approx.)

PRECAUTIONS & PRESERVATION


- Do not use it on plastic materials.
- To be used in conditions of good ventilation.
- Do not apply at temperatures below 12°C or above 25°C.
- Do not apply in direct sunlight.
- DANGEROUS. OBSERVE THE PRECAUTIONS FOR USE.
- Keep it out of reach of children
- Store in the original package, carefully closed after use.
- Store away from frost, heat and moisture.
- The Safety Data Sheet for this product is available on our website www.interkas.gr, www.blanchon.gr

TOOL CLEANING

- Immediately after use with water (preferably hot) or WS.
- Close the container tightly after use.
- Dispose of the containers at a waste reception center.
- Do not dispose of residue in the drain.

TOOLS & CLEANING

TOOLS



TOOL CLEANING



White Spirit