

Blanchon

Quality is in our nature



Blanchon Wood Saturator-DECKING OIL

Blanchon DECKING OIL is intended for the protection of all types of wood (autoclaved or not) commonly used outdoors: European hardwoods, exotic woods, softwoods (including red cedar). Naturally penetrating Blanchon DECKING OIL is particularly suitable for the protection of wood items that are difficult to impregnate such as ipé, iroko, sipo, teak (for very rare items, consult our Technical Services).

The application of Blanchon DECKING OIL is done with the "liquid-to-liquid" technique, creating a nutrient protection that does not peel and is easily maintained.

Blanchon DECKING OIL emphasizes, with its matte finish, similar to that of "oiled wood", the natural elegance of wood.

1

STEP

PREPARATION

- **New Exotic Wood:** Degrease* with a cloth soaked in acetone.
- **Old raw wood, stained or greyed:** clean using Syntilor's Dégriseur Bois greyed wood cleaner.
- **Old finishes (old paints, varnishes ...):** sand with sandpaper 40, 60 and then 100 or remove old substrates with Syntilor's corrosive Décapant.
- If necessary, apply a coat of wood-eating insect-resistant woodworking product.

Note:*The new exotic woods are recommended to be initially exposed to the sun and weather conditions for about 6 months, in order to open the pores and receive deep impregnation with DECKING OIL. The same applies to autoclaved wood.

PRO ADVICE

A light sanding (80-100 sandpaper), before application, on all surfaces, will open the pores and facilitate penetration.

2

STEP

APPLICATION

- Mix well before and during use, do not dilute.
- Apply the product in 2 rich and consecutive layers with the "liquid to liquid" technique until the wood is "denied", i.e. until the saturated wood cannot absorb another product always in the direction of the wood fibers (soak the grooves, joints and ends well).
- Let it penetrate for 5-10 minutes, then wipe off excess material with a clean cotton cloth.
- If necessary and in cases of weathered woods, apply a new layer of product to give an even appearance.
- Allow the saturated wood to stabilize for about 3 days before use.
- Clean the application tools immediately after use with White Spirit.
- **Μαζέψτε τα πανιά που χρησίμευσαν στο σκούπισμα αμέσως μετά τη χρήση και μην τα αφήνετε στον ήλιο (κίνδυνος αυτο-ανάφλεξης υφασμάτων διαποτισμένων με λάδι). Τα πανάκια μπορούν επίσης να φυλάσσονται μέσα σε νερό.**

3

STEP

MAINTENANCE

- Μόλις soon as the surface of the wood begins to open naturally from weather conditions and UV radiation, apply **Blanchon DECKING OIL** directly to the bleached areas.
- In case of delayed maintenance, clean first with **Syntilor's Dégriseur Bois** greyed wood cleaner.



TECHNICAL FEATURES

RESIN	SPECIAL REINFORCING RESIN, FOR THE PROTECTION AND DECORATION OF EXTERIOR TIMBER
DENSITY (at 20°C)	0,88 (± 0,03)
COMPOSITION	Liquid
DRYING TIMES (at 20°C)	Between Layers : 6 Hours Dry: 24 hours In use : 72 hours
YIELD	4-8m ² /L (for 2 layers)
ΟΨΗ	Ματ

PRECAUTIONS & PRESERVATION

- Do not apply wood paints or impregnation varnish in advance.
- Make sure that the wood is dry: at least 2-3 days of good weather before application and that there is no risk of rain within the first 24 hours after applying the 2nd layer.
- Use outdoors only or in a well-ventilated area.
- Do not apply at temperatures below 12°C or above 25°C.

- Keep it out of reach of children
- Store in the original package, carefully closed after use.
- Store away from frost, heat and moisture.
- The Safety Data Sheet for this product is available on our website www.interkas.gr, www.blanchon.gr

TOOLS & CLEANING

TOOLS



TOOL CLEANING



White Spirit