



Evolución Constante

Ctra. Masía del Juez, 36 46909 TORRENT (Valencia) SPAIN TEL: (34) 961 550 073 FAX: (34) 961 573 720 E-mail: blatem@blatem.com visítenos en: www.blatem.com

Fichas Técnicas



BLATEM CHALK PAINT



DESCRIPTION

Water-based paint whose special formula allows a chalk effect finish on indoor furniture with very easy sanding.

PROPERTIES

Water-based paint with a very weak smell, very easy to apply and very easy to sand, which allows to obtain the high decoration chalk effect finish.

APPLICATIONS

For decoration and crafts in interiors on any properly prepared surface (wood, plaster, cement, brick, stone, etc.) where this decorative finish is desired.

TECHNICAL FEATURES

Appearance: Matte.

Colors: White and 12 colors.

Fineness : 6.0 ± 1 HG.(Hegman Degrees) (UNE-EN-ISO 1524).

Repainting: 4-6 hours.

Viscosity: 115 ± 10 U.K. (Krebs Units) at $25^{\circ} \pm 10^{\circ}\text{C}$ (UNE 48-076).

Density: 1.60 ± 0.10 gr/cc (UNE-EN-ISO 2811-1).

Coverage: Excellent.

Adhesion: excellent. **Yield:** 8-11 m²/lt

and hand. **Drying:** 30 to 60 minutes.

Utensils: Cleaning with water.

Shelf life: More than one year in original closed packaging.

Non-flammable.

C.O.V.; 2004/42/II(A/a) (75/30) Max. COVS: 15G/L.

SURFACE PREPARATION

Surfaces should be clean, dry, and properly prepared before applying Blatem Chalk Paint.

If the surface is painted with tempera or lime, remove it beforehand and if it is painted with quality paint, remove the parts that are in poor condition.

HOW TO USE

Blatem Chalk Paint is applied by brush, roller or airbrush gun with low dilution: brush or roller 5-10%, gun 15-20% drinking water.

As Blatem Chalk Paint is easily sandable we can first apply a base color and then a second coat of another

color that contrasts with the one below.

Depending on the areas and intensities of the sanding, this is how we will obtain the type of finish. It is important that the paint is completely dry before sanding.

If we want a wax finish, we will apply a cotton cloth or sponge brush on Blatem Chalk Paint, offering a handmade look.

To get an aged look we will apply our Drak Chalk Paint Finishing Wax. To finish we will polish with a cloth until we obtain the desired shine.

If the painted surface is going to have a lot of use, apply a coat of Matte Chalk Paint Varnish for greater protection.

RECOMMENDATIONS

-Do not apply with temperatures below 8°C and relative humidity above 80%.

-Remove the contents of the container.

-Avoid direct exposure of the packaging to the sun and frost.

PRESENTATION

In 500ml containers. Colors:
white and 12 colors.

STORAGE

Storage time: more than a year in its original container well closed and protected from the weather (covered and temperature between 5 and 35°C).

SAFETY TRAINING

It is essential to follow the instructions on the package label. For more information, please refer to the product safety data sheet.

DATE...: 02/02/123

The data provided in this technical sheet have been made by the technical services of this company and must be followed for a correct application of the product.

As the application is carried out by the client outside the possibility of control of this company, in the event of not following the instructions indicated, it will be the exclusive responsibility of the client.

It will also be the responsibility of the customer not to take appropriate measures in order to comply with current legislation.

The information contained in this technical sheet responds to the knowledge of the product in tests carried out by the technical services of this company. However, taking into account that paints in certain circumstances are beyond our control, especially in their application, we can only guarantee the quality of the paint, and this company reserves the right to modify the content of the data in this technical data sheet without prior notice.
