

Syntilor



DECKING OIL NEPOY - SATURATEUR ULTRA PROTECT

HIGH PROTECTION WATER base DECKING OIL It impregnates, constantly protects and decorates all wooden terraces and decks. Easy and economical application: directly on new wood without prior 6 months of natural aging, no need for sweeping. 2 coats are enough for a time-resistant result.

- For all species: exotic woods, European timber (hardwood, soft resin wood or other softwood), impregnated timber
- For wooden terraces, decks and surrounding pool area etc.
- Especially for Outdoor Use

1

STEP

PREPARATION

- **New Exotic Wood:** Degrease with a cloth soaked in acetone.
- **Old raw wood, stained or greyed:** clean using Syntilor's Dégriseur Bois greyed wood cleaner.
- **Old finishes (old paints, varnishes ...):** sand with sandpaper 40, 60 and then 100 or remove old substrates with Syntilor's corrosive Décapant.
- If necessary, apply a coat of wood-eating insect-resistant woodworking product.

'PRO ADVICE

A light sanding (80-100 sandpaper), before application, on all surfaces, will open the pores and facilitate penetration.

2

STEP

APPLICATION

- Mix well before and during use, do not dilute.
- Apply a 1st thin coat in the direction of the wood fibers (soak the grooves, joints and ends well).
- Let it penetrate for 20 to 30 minutes.
- Apply the 2nd thin coat as soon as the wood loses its "wet" appearance. Use the brush to pick up any excess product to avoid traces of dripping or shine on the surface. **NO NEED TO WIPE**
- Surfaces are given for use 12 hours after application.

3

STEP

MAINTENANCE

- As soon as the surface of the wood begins to open naturally from weather conditions and UV radiation, apply **Syntilor High Protection Water Decking Oil** directly to the bleached areas.
- In case of delayed maintenance, clean first with **Syntilor's Dégriseur Bois** grayed wood cleaner.

TECHNICAL
FEATURES
PRECAUTIONS
& PRESERVATION
TOOLS
& CLEANING




CONÇU & FABRIQUÉ
EN FRANCE

DENSITY (at 20°C)	1,02 (± 0,03)
COMPOSITION	Liquid
DRYING TIMES (at 20°C)	Between layers: 20' to 30' minutes In use : 12 hours
YIELD	10-12m ² /L ανά στρώση
ASPECT	Matt

- Do not apply wood paints or impregnation varnish in advance. Do not apply over freshly washed other Decking oil.
- Make sure that the wood is dry: at least 2-3 days of good weather before application and that there is no risk of rain within the first 24 hours after applying the 2nd layer.
- Use outdoors only or in a well-ventilated area.
- Do not apply at temperatures below 12°C or above 25°C.
- Keep it out of reach of children
- Store in the original package, carefully closed after use.
- Store away from frost, heat and moisture.
- The Safety Data Sheet for this product is available on our website www.Interkas.gr or www.syntilor.com

TOOLS



TOOL CLEANING

