



Avenue Vésale 20B 1300 WAVRE (Belgium), T. 32 (10) 23 82 80, F. 32 (10) 23 82 89

EASY COLOR ACRYLIC VARNISH

TECHNICAL SPECIFICATIONS

NAME	E.C.ACRYLIC VARNISH
TYPE	Special type acrylic varnish.
USE	It is used for the protection against oxidation, of metallic paints (gold, silver, copper, etc.) as well as for any metal surface externally and internally.
FEATURES	specific gravity: 0.85 ± 0.05 gr/lit at 20 ° C Yield: 14-18 m ² /lit per layer (may vary depending on roughness, surface absorbency and application method) Colourless semi-gloss appearance Solids By Volume: 29.5% ± 2 By Weight: 24.5% ± 2 Vapour Permeability - Keeping: Keeps for at least 2 years Composition: 100% Acrylic resins and aromatic hydrocarbons Packaging: LT. 0.5 surface: 30' at 20°C Repainting: 12 hours at 20°C depth: 18 hours at 20°C
DRY	It is suitable for application on interior and exterior surfaces, on top of other colors, copper, gold, silver, as well as over fluorescent paints. Protects metal surfaces from oxidation.
SURFACE PREPARATION	Dilution: 5-10% dilution with WS Application tools: with brush or short-haired mohair roller
PREPARATION OF THE PRODUCT	Layers: one (1) or two (2) layers Apply 1 or 2 coats with a brush or roller.
APPLICATION	

NOTES:

The application temperature should be between +10°C and +30°C. Wash the tools immediately after use. It can be kept for at least 2 years in its closed original packaging.

Water varnishes EU VOC limit for this product (Cat.D/e): 400 g/l (2010) Maximum VOC content 400 g/l
Containers and material residues must be disposed of in accordance with local and national regulations.