



EASY COLOR GOLD & SILVER

TECHNICAL SPECIFICATIONS

NAME E.C.GOLD & SILVER

TYPE Gold and silver metallic paint

USE It is used for outdoor and indoor use. Applied to: wood and wood derivatives,

gypsum and drywall, metal surfaces, non-metallic metals (properly prepared). Prepare the bare spots with the appropriate primer and then apply 1 or 2

coats of E.C Gold or Silver.

specific weight: Gold 1,210 ± 0.05 Kg/lt at 20°C

FEATURES Silver 0.980 ± 0.05 Kg / lt στους $20 \degree$ C

Yield: 16-20 m²/lt per layer (may vary depending on

roughness, surface absorbency and application

method)

Semi-Gloss Gold (one shade) and Silver

Solid Gold By Volume: $22.6\% \pm 2$ By Weight: $44.3\% \pm 2$ By Volume: $18.8\% \pm 2$ By Weight: $28.9\% \pm 2$

Dry thickness 10m on average

Keeping: Keeps for at least 2 years

Composition: 100% Acrylic resins, aromatic hydrocarbons and

bronze and aluminum powder

Συσκευασία: LT. 0,125L - 0,25L - 0,5L

surface: 10'-30' at 23°C
Repainting: 12 hours at 23°C
depth: 18 hours at 23°C

Dilution: With brush or short mohair roller: without dilution

PREPARATION OF THE

PRODUCT

DRY

With spray gun: from 5 to 20% with binary **Application tools:** with brush or short-haired mohair roller, paint gun

Layers: one (1) or two (2) layers

APPLICATION Apply 1 or 2 coats with a brush or roller. Apply a preparation primer to the

bare metal spots, then apply E.C Gold or Silver. To prevent oxidation, apply a

coat of E.C Acrylic Varnish.

NOTES:

The application temperature should be between +10°C and +30°C. Wash the tools immediately after use. It can be kept for at least 2 years in its closed original packaging.

Containers and material residues must be disposed of in accordance with local and national regulations.