

WOOD GRAIN EFFECT ENAMEL

TECHNICAL BROCHURE

NAME	WOOD GRAIN EFFECT ENAMEL
DESCRIPTION	Premium quality polyurethane composition wood imitation paint for indoor and outdoor use, made with the most advanced technology for maximum performance. It exhibits very good hardness, great coverage, performance, smooth surface and easy application. Satin finish. It is washable and highly resistant to abrasion, scratches, cleaning products, liquid stains, etc. Colors that blend with each other and are weather-resistant.
PROPERTIES	Ideal for reproducing a beautiful and realistic wood effect on all kinds of masonry surfaces, wood and iron where they are properly prepared, or to decorate with a single layer of doors, windows, shelves, cabinets, household appliances, etc., both indoors and outdoors. Finish: Satin Color Spread: Excellent Workability: Excellent
APPLICATION	Shades: 6 wood colors Coating: 24 hours Durability: Excellent. Coverage: Excellent Drying time: 4-6 hours at 25 ± 8°C. Viscosity: 150 +/- 50" F-4 (Ford Cup nº4) at 25 ± 8°C (ASTM D-1200). Density: 1.35 ± 0.10 g/cc (UNE-EN-ISO 2811-1 and 2). Yield: 9-12 m ² /L per layer. Hardness: Good Storage: Over one year in the original closed package. Tool Cleaning : With WS
FEATURES	WTO: 2004/42/II (S/I) (500). Maximum volatile organic compound content: 450 gr/L New surfaces: For wall or wood, apply a previous coat of primer and rub lightly. For iron, first apply a coat of primer of Blatprimer Antioxidante Ignífuga (Refractory Antioxidant Primer) or a multi-purpose primer or a metal primer. Painted surfaces:
SURFACE PREPARATION	- If the paint is in poor condition, remove it, repair the defective areas and follow the appropriate application as for the new surfaces. - If the paint is in good condition, wash, sand the surface and apply the Imitation Wood Paint enamel (Esmalte Efecto Veta de Madera) directly.
APPLICATION	Apply the product unevenly with a brush, leaving a rich layer of product. Apply the product with the brush and finish with long pulled strokes, creating the desired effect and wood veneers. The product can be processed up to 10 minutes after application. The wood effect and veneers can be marked using a brush, irregularly cut. The joints must be parallel to the wood veneers.
RECOMMENDATIONS	After use, close the container being careful to allow some air if the product needs to be used again. Stir the contents of the container until the product is homogenized.
PACKAGING	Available in the following shades: Sapele, Light Drys, Walnut, Drys, Light Walnut, Ebony, Mahogany, Drys ash
STORAGE	It can be kept for at least 1 year in its closed original packaging, protected from heat and cold (at a temperature between 5 - 35°C).
SAFETY INFORMATION	Follow the instructions on the package label. For more information, consult the product safety data sheet. Keep out of reach of children.

DATE

: 13/02/18

The data provided in this data sheet has been produced by our company's technical services and must be kept for the correct application of the product.

Applications made by the customer outside of the predetermined instructions and without the possibility of control or prior agreement on the part of our company, will be under the sole responsibility of the customer.

It will also be the customer's responsibility to take appropriate measures to comply with applicable legislation. The information contained in this technical sheet is based on knowledge of the product following tests carried out by the company's technical services. But bearing in mind that local applications are beyond our control under certain circumstances (especially in their applications), we cannot guarantee anything more than the correct product quality. Our company reserves the right to modify the content of the data in this technical sheet without prior notice.