

FRAMMENTI

TECHNICAL SPECIFICATIONS

NAME	FRAMMENTI
TYPE	FRAMMENTI is a protective water-varnish finish, with a glossy effect, containing aluminum flakes (glitters) and is suitable as a final protection for murals, acrylic paints, decorative style products, etc.
USE	It is used as a protective-decorative, finish-varnish after most of the style products of Giorgio Graesan & Friends.
FEATURES	specific weight: 1,01 ± 30 gr/lit at 25 ° C Yield: 10-12 m²/lit per layer (may vary depending on roughness, surface absorbency and application method) Glossy appearance pH 9 Vapour Permeability - Keeping: Keeps for at least 2 years Colors: - Packaging: LT. 1 and 2.5 surface: 60' at 20°C Repainting: 3-4 hours at 20°C depth: 6 hours at 20°C
DRY	
SURFACE PREPARATION	Frammenti is suitable for application on interior walls. It can be used on clean, dry surfaces, without traces of grease.
PREPARATION OF THE PRODUCT	Dilution: ready to use (in some application cases (such as in Spirito Libero) it can be diluted up to 90% with water.
FEATURES & DURABILITY	Application tools: with brush or short-haired mohair roller Layers: one (1) or two (2) layers Frammenti offers washability. It is suitable for protecting interior surfaces.
APPLICATION	Apply 1 or 2 coats with a brush or roller. VETRO can also be applied over tiles.

NOTES:

The application temperature should be between +10°C and +30°C. Wash the tools immediately after use with soap and water.

It can be kept for at least 2 years in its closed original packaging.

Does not contain solvents – Does not ignite – Breathable

Regulations – Information

Water varnishes EU VOC limit for this product (Cat.A/e): 130 g/l (2010) Maximum VOC content 20 g/l

Containers and material residues must be disposed of in accordance with local and national regulations.

Publication - April 2016