



LASURE U.H.P. – ORGANIC IMPREGNATION VARNISH

Lasure U.H.P. Ultra-High Performance Organic Formulation* and ECO Protection Impregnation Varnish sustainably protects and decorates external vertical wood paneling. It contains 86% natural*, mineral and organic ingredients. The quality of the ECO Protection series formulations is recognized by AFPRAL, which recommends this product to reduce the risks of respiratory allergies.

* Tested according to NF EN 16640 and not from organic farming

- Very high resistance to UV radiation and bad weather conditions
- Microporous and water-repellent: waterproof and allows wood to breathe
- Ideal for large surfaces: compound-free result

1

PREPARATION

- **New or raw wood:** perfect adhesion to bare, clean, dry and healthy wood (degrease exotic woods in advance).
- **Grey or blackened wood:** clean with Acetone or other degreaser and then scrub with sandpaper (etc.80).
- **Wood with pre-existing other impregnation varnish:** rub lightly with sandpaper (co.120).
- **On old finishes (paints, varnishes, etc.):** scrub successively with sandpaper etc. 40, 60 and then 100 mm or use corrosive to reveal clean wood.
- Dust carefully.
- If necessary, treat with a suitable woodworking product against wood-eating insects.

2

APPLICATION

- Ready to use Do not dilute.
- Mix well before use.
- Apply with a brush, wide brush or paint gun, always in the direction of the wood fibers.
- **On new or bare wood:**
 - Outside: Three (3) layers.
 - Inside: Two (2) layers.
- **In old wood or with pre-existing wood impregnation varnish (after sufficient preparation):**
 - In good condition: one (1) coat is enough
 - In poor condition: two (2) layers
- Scrub with sandpaper before the last coat (120 to 180 coats) to eliminate the slight roughness on the wood and get a beautiful look.
- Do not exceed 48 hours between 2 layers.



TECHNICAL FEATURES

RESIN TYPE	Water Polyurethane Resin
DENSITY	Approx. 1.03
COHERENCE - RECOMMENDATION	Milky
DRY TIME (at 20°C)	In contact : 30' minutes Between layers : 4 hours Full: 12 hours
PERFORMANCE	12 m ² per Liter per layer
SIDE	Satin
HEALTH LABEL	ÉMISSIONS DANS L'AIR INTÉRIEUR *Information on the level of emission of volatile substances into indoor air, posing a risk of inhalation toxicity, on a class scale ranging from A+ (very low emissions) to C (high emissions)
ECOLABEL	U.H.P Impregnation Varnish is certified with an eco-label for outdoor use.

PRECAUTION & CERTIFICATION

- Apply to healthy, clean, non-greasy and dry wood (where moisture is less than 10%).
 - Do not apply to parquet and wooden floors.
 - Outdoors, the "colorless" shade is only used for finishing or renovating wood already impregnated with another colored shade.
 - It is recommended to use an anti-dust mask during scrubbing operations.
 - It is only used outdoors or in a well-ventilated area.
 - Do not apply at temperatures below 12°C or above 25°C.
-
- Keep out of reach of children.
 - Store in the original packaging, carefully closed after use.
 - It is kept away from frost, heat and moisture.

TOOLS & CLEANING

TOOLS



TOOL CLEANING

