



LOFT ORIGINAL

TECHNICAL SPECIFICATIONS

NAME

LOFT ORIGINAL

TYPE

Decorative paint – Paint of PRESSED CEMENT MORTAR for walls and floors.

USE

Water product for indoor use.

FEATURES

specific weight: 1.68 ± 30 gr/lit at 25 ° C

Viscosity: = = =

Yield: 6-7 m²/lit (may vary depending on roughness, surface absorbency and application method)

Aesthetic result: Matte pressed cement mortar

Colors: The colors from the catalog

Packaging: LT. 2.0

surface: 2 hours at 20 ° C

Repainting: 4 hours at 20°C

depth: 24 hours at 20 ° C

DRY

FEATURES & DURABILITY

It is a modern and elegant decorative watercolor for indoor use. LOFT ORIGINAL can be applied to walls as well as floors. Thanks to its unique colors and shades, it can be used to create extremely contemporary and modern living spaces. LOFT ORIGINAL is a high quality product, washable and that can be repainted with any other water-based color.

ENVIRONMENTAL PERFORMANCE

PERFORMANCE	REGULATION	VALUE	TYPE
EMISSION OF INTERNAL POLLUTION SUBSTANCES TYPE R	ISO 16000	TVOC<1 Mg/mc3 CATEGORY A+	
WTO In the final product ready to use	REGULATION 2004-42-EC	Maximum 2g/L (EU maximum 200 g/L) Cat. Y/I	

SURFACE PREPARATION

On walls, apply a coat of **Thick Paint Preparation Primer - PRIMAIRE AVANT ENDUIT**.

On floors with cement mortar or tiles, apply a coat of Loft Primer for cement mortar and tile floors – LOFT PRIMAIRE & LISSAGE.

On countertops and wall tiles, apply a coat of Loft Primer for worktops and wall tiles – LOFT PRIMAIRE PLAN DE TRAVAIL.

Follow the instructions on the product containers.

Dilution: Ready to use.

PREPARATION OF THE PRODUCT

Stainless steel spatula.

APPLICATION TOOLS

Layers: 2 layers

LAYERS

Mix well before application.

APPLICATION

Apply a very thin and homogeneous layer with a spatula or the stainless steel top handle spatula. Allow to dry ± 4 hours.

Apply the 2nd coat with the same coloring, making cross-sectional movements. Without waiting for it to dry, smooth as you proceed with the spatula, in all directions, until you achieve a very smooth surface. Allow to dry for about 24 hours.

TWO-TONE: Choose the 2 LOFT ORIGINAL colors you wish to combine. Apply a very thin and homogeneous coat of the darkest coloring with a spatula or the stainless steel top handle spatula. Allow to dry ± 4 hours.

Apply the second coat, applying the 2 colors at the same time, to bands ± 50 cm wide. Create vertical, irregular zones, smoothing as you go with the spatula so that the two colors fade into each other. Apply the light color onto the dark color and vice versa until you achieve the desired effect. Finish smoothing with the spatula, with long movements from top to bottom. Allow to dry for about 24 hours.

After the special protector has been applied, the LOFT ORIGINAL paint will be washable. For particularly durable protection, use the **Loft Protector for floors, showers and work surfaces**. On the wall, use the **mat Loft Protector**.

NOTES:

The application temperature should be between $+5^{\circ}\text{C}$ and $+30^{\circ}\text{C}$. Wash the tools immediately after use with soap and water.

It can be kept for at least 2 years in its closed original packaging.