

Syntilor



HIGH PROTECTION XYLODHONE® LASURE – 8 YEARS

LASURE XYLODHONE IMPREGNATION VARNISH 8 years is intended for the protection and decoration of all exterior and vertical wood coverings. Its excellent covering capacity enhances the durability of the surface offering long-lasting durability. Thanks to its gel texture, it offers better application comfort.

- For all types of wood*
- Vertical and horizontal** wood cladding
- Outdoor – Indoor use

1

STEP

PREPARATION

- **New or rough wood:** perfect adhesion to bare, clean, dry and healthy woods (in the case of exotic wood, degreasing is required in advance).
- **Grayed or blackened wood:** clean with Dégriseur Bois Syntilor cleaner, then scrub with sandpaper (etc. 80).
- **Wood that already has another impregnating varnish:** lightly rub with sandpaper (120 etc.). **Note:** Syntilor Xylodhone® Lasure can be applied to all types of old soaking varnishes.
- **Wood with old finishes:** scrub successively with sandpaper etc. 40, 60 cm and then 100 mm or with the use of corrosive resemble the wood complete.
- Dust carefully.
- If necessary, treat the surface with a suitable product against wood-eating insects.

2

STEP

APPLICATION

- Mix well before use, do not dilute the product.
- Apply with a brush, wide brush or paint gun always in the direction of the fibers Wood.
- **On new or bare wood:** Outdoors: three (3) layers.
- **On old wood with pre-existing other impregnation varnish:** In good condition: one coat is enough.
- **In poor condition:** scrub the problematic surfaces with sandpaper co.120, remove the dust and then apply two coats.

NOTE: Sand between layers (sandpaper etc.120 to 180) to eliminate small wood rusts so that you have a very good look.



LASURE XYLODHONE® ΥΨΗΛΗΣ ΠΡΟΣΤΑΣΙΑΣ – 8 ΧΡΟΝΙΑ

TECHNICAL
FEATURES

TYPE OF RESIN	Water Polyurethane Resin
DENSITY (20°C)	1.05 (±0.05 depending on hue)
COHESION	Creamy liquid
DRY (at 20oC, 65% humidity)	To the touch: 45'-1 hour Between 2 layers : 2 hours Fully : 12 hours
PERFORMANCE	12m2/L per layer Satin or Matte
SIDE	

TOOLS
& CLEANING
PRECAUTIONS
& PRESERVATION

- To be used in a well-ventilated area.
- Do not apply at temperatures below 10°C or above 25 ° C. The wood should not have a moisture content of more than 10%.
- Keep out of reach of children.
- Store in its original packaging for 2 years, carefully closed after use.
- Store away from frost, heat and moisture.
- The Safety Data Sheet for this product is available on our website www.interkas.gr or www.syntilor.com

TOOLS



TOOL CLEANING

