



OCEANIC Parquet Sealer - Air Protect

Water Floor Varnish **Blanchon Oceanic**

Air protect It is of pure polyurethane composition and provides long-lasting protection to wooden floors from chemical and mechanical damage, leaving the wood in its natural color. Its technical performance and composition, with a very low VOC content, comply with the highly selective environmental requirements of the European Ecolabel. Floor varnish **Blanchon Oceanic Air protect** A product of the latest in professional floor coating technology, it is enhanced by Air Protect® technology: a real innovation that improves indoor air quality, thanks to a formaldehyde absorption agent. **Air Protect Innovation**: blocks 80% of formaldehyde emissions coming from the floor, absorbs up to 40% of formaldehyde emissions in the room (laboratory test: comparative measurements taken in a single room over 28 days).

- High efficiency is applied to wooden parquet floors of all kinds (rarely to exotic woods, if you are going to contact us).
- Indoor use only

PREPARATION

1

STEP

- Océanic Air Protect floor varnish should be applied to wooden floors that have previously been sanded well or up to bare wood (cleaning with corrosive is not recommended), which have been cleaned of dust and all traces of detergent, grease, wax, varnish or linoleum (or other special oils).
- The wooden floor must be completely clean and dry. As a general rule, the percentage of wood moisture should be below 10% (do not use detergents, bleaches or wood floor cleaners).
- Remove all traces of dust.
- Treatment against wood-eating insects: Use only therapeutic products that are proposed by Blanchon.
- Wood coloring: Wood floors that have been sanded down to bare wood can be painted with Teinte Bois water paint or Blanchon Wood Ageing Agent. After using these products and after they have dried, apply a coat of Blanchon Preplast® Primer to insulate the paint.
- In all cases, do not rub the paint. It is recommended to sand the wooden floor before applying the final coat of **Océanic Air Protect**, after the previous coat has dried completely (about 2 hours). Carefully remove all traces of dust before applying the final coat of **Océanic Air Protect**.
- Using a Blanchon primer as the first coat allows for the quick application of 2 coats **Océanic Air Protect**, thus saving time.

APPLICATION

2

STEP

- Ready to use, do not dilute.
- Shake the package well before use.
- Apply with a brush, brush, or roller 3 even and well-"filled" layers.
- Leave to dry for 1 hour between each layer, then rub lightly (sandpaper 120 to 180) and dust well. Do not exceed 48 hours between 2 layers.
- Reuse spaces within 12 hours after the last layer. Take a few precautions during the first 7 days. Do not lay carpets for 10 days.
- **MAINTENANCE: Daily cleaning:** Use Nettoyant Parquets Vitrifiés et Stratifiés Syntilor frequently and regularly. **Occasional maintenance:** Use Savon Raviveur Parquets Vitrifiés et Stratifiés Syntilor. **Annual renovation:** to reshape and give a protective layer and hide scratches and traces of wear, use the Rénovateur Vitrlor® Parquets Vitrifiés et Stratifiés Syntilor.



Blanchon
Quality is in our nature

CONÇU & FABRIQUÉ EN FRANCE

TECHNICAL CHARACTERISTICS

RESIN TYPE	High Grade Water Polyurethane Resins
MEASUREMENTS ON	50 cm (400g MandreL) (according to the French standard T 30039)
SCRATCH RESISTANCE	7 hours, with a pencil.
TABER ABRASION RESISTANCE	Weight loss: 28 mg (CS10 wheel, 1000 rpm, 1 kg)
DENSITY (at 20°C)	1.05 (± 0.05 depending on the aspect)
RECOMMENDATION	Liquid milky
DRYING TIMES (at 20°C)	To the touch : 30 minutes Between layers: 1 hour Fully: 12 hours
PERFORMANCE	10 m ² per litre per layer
SIDE	Satin, Glossy
IMPORTANT NOTE	 *Information on the level of VOC emissions in indoor air, presenting a risk of inhalation toxicity, on a scale ranging from A+ (very low emissions) to C (high emissions)

ECOLABEL

TOOLS & CLEANLINES PRECAUTION & STORAGE

- Do not apply to pre-polished factory floors.
- Application to wooden floors, clean, dry and without traces of waxes, varnishes, detergents, greases, linoleum (or other special oils) or polishes.
- To be used in a well-ventilated area.
- Do not apply at temperatures below 12°C or above 25°C.
- Keep it out of reach of children
- Store in the original package, carefully closed after use.
- Store away from frost, heat and moisture.
- The Safety Data Sheet for this product is available on our website www.interkas.gr, www.blanchon.gr

