



FLEUR DESIGNER'S PAINT SPRAY METAL

COLORIFICIO CENTRALE S.r.l.
Via Industria 12,14,16
25030 Torbole Casaglia (BS) ITALY
C.F e P.IVA 03032510178

TECHNICAL DATA SHEET

Description:

Metallic water-based paint spray, high coverage and quality, rich in minerals, ideal for indoor and outdoor use.

Application:

Thanks to the product's characteristics, we recommend using it as a finishing finish or as a base layer for other applications.

- For DiY use
- For Decoration
- Does not contain lead or heavy metals
- Very strong color coverage and fastness
- Easy to use and repaint
- For household use
- Use for garden decoration

Instructions:

- Shake the spray well before use, for at least one minute after listening to the sound from the stirring balls of the container.
- Apply it in thin layers to achieve better results, three thin layers are better than one thick layer. Repaint after 30 minutes.
- After use, rotate the container upside down and press the valve for several seconds until only gas appears to prevent clogging.
- Do not spray on clogged equipment and only use it in well-ventilated areas.
- The DDA is given upon request.

Features:

- Quick drying
- Adheres very well to any surface



FLEUR DESIGNER'S PAINT METALLIC SPRAYS

COLORIFICIO CENTRALE S.r.l.
Via Industria 12,14,16
25030 Torbole Casaglia (BS) ITALY
C.F e P.IVA 03032510178

- Very Covert
- Can be used indoors
- Easy to apply and paint

Composition: Modified Polyurethane resins

Color: Color Chart

Gloss: (60°) > 70% glossy

Dry to the touch: (ASTM D-1640 ISO 1517) 30' minutes

Fully Dry: (ASTM D-1640 ISO 1517) 24 hours

Dry film thickness: 20 m/layer (2 layers)

Theoretical yield: 2.0m² - 300ml spray container

Solvent: Water and Alcohols

Lifespan: >2 years

Repaint: After 30'

Temperature resistance: Not specified.

Application conditions: T° Therm. Ambient (min): 8°C - T°
Surface Temperature (min): 5-50°C | Humidity max: 85%

Propulsive: DME

VOC(g/l) 525-460 (Depending on the shade)