

Bio-based paint specially designed to withstand wet spaces and surfaces of high use and pressure. Ideal for the sustainable renovation of furniture, worktops and kitchen sinks, tiled walls, bathroom countertops, etc.

- Very High adhesion to raw, varnished or painted wood, melamine, formas, laminate, wall tiles
- Very High resistance to water splashes, condensation, stains and greases: does not clog pores
- Withstands heat and room temperature fluctuations ($10^{\circ}C 40^{\circ}C$)
- Anti-vibration and anti-scratch: flexible and durable laminate film-film.
- Highly washable, category 1 (EN 13 300 standard): easy daily cleaning with water and neutral detergents without altering the film/film and shades.
- It contains 76% natural, mineral and ingredients of organic origin (not from organic farming), including 25% carbon of organic origin measured according to the NF EN 16640 standard.
- Circular economy: Formula containing at least 1% (SATIN appearance) and 7% (matte appearance) of recycled egg shell powder. Packaging containing at least 30% recycled plastic.

PREPARATION

Before applying the paint, remove any silicone sealant present on the surface and repeat the silicone application after the paint has completely dried.

- On painted, varnished or impregnated wood, melamine, laminate: sand the surface (sandpaper etc. 120), dust well and clean well with acetone.
- On raw wood: sand the surface (sandpaper co.100-120) and dust well.
- On tannic woods (oak, chestnut, etc.), apply a substrate suitable for the color Renov' Cuisine & Bain Matt, especially in light shades.
- On oiled or waxed wood: sand the surface with sandpaper in successive coke 40, 60 after 100, dust well and clean well with acetone.
- On wall tiles, tiled countertop: degrease with acetone, paying special attention to joints and taking care to eliminate any trace of residue and mold. PRO TIP: on smooth tiles, roughen the surface by sanding with 100-120 grit sandpaper to break the gloss on the surface and promote the adhesion of the Renov' paint.
- On painted walls, plaster, plaster, wallpaper (in good condition): remove parts that do not have good adhesion, remove dust.
- On water-repellent placard surfaces: dust off and apply a suitable substrate.

APPLICATION

Apply to healthy, clean and dry surface

- Mix well before use to homogenize the color.
- Start by painting the corners, corners, and joints with a brush.
- Apply evenly with PEINTURE RENOV' CUISINE & BAIN with the microfiber ripolin roller, apply a 1st coat from top to bottom, crossing the passes. Allow to dry for 2 hours.
- Apply a 2nd coat in the same way.

Dries and hardens quickly after 12 hours (48 hours are required for indoor shower): Take some precautions in the first few days (bumps, stains, cleaning, etc.). All performance is achieved after 10 days of drying.





DENSITY (at 20°C)	1,15 -1,25
COHERENCE - RECOMMENDATION	Milky
DRY TIME (at 20°C)	Between layers: 2 hours
	Fully: 12 hours
PERFORMANCE	12 m² per litre per layer
SIDE	Satin & Matte
HEALTH LABEL	* Emission level information of volatile substances in the air of indoor areas that present a risk of toxicity inhaled, on a scale of a variable class from A+ (very low emissions) to C (high emissions)

This paint is not INSULATING. Do not apply to shower floors and indoor bathtubs, floors, sinks, sinks, horizontal surfaces (except worktops). Do not apply RENOV' Cuisine & Bain MAT Finish Renovation Paint to tile or wall surfaces inside showers. White marks may appear on your surfaces when in contact with water or other liquid product, which will disappear after drying.

- Use in a well-ventilated area.
- Do not apply at temperatures below 12°C or above 25°C.
- Keep out of reach of children.
- Dispose of the contents of the container in an approved landfill.
- Do not throw debris down the drain. Keep out of frost.
- The Safety Data Sheet for this product is available on our website www.syntilor.com

TOOLS

TOOL CLEANING









Syntilor