



NACRE

TECHNICAL SPECIFICATIONS

NAME

NACRE

TYPE

Decorative color with a delicate pearlescent velvet finish.

USE

Water product for indoor use.

FEATURES

specific weight: 1.35 ± 30 gr/lit at 25 ° C

Viscosity: = = =

Yield: 12 m²/lit (may vary depending on roughness, surface absorbency and application method)

Aesthetic result: delicate pearlescent velvet finish

Colors: The colors from the catalog

Packaging: LT. 2.0

surface: 2 hours at 20 ° C

Repainting: 4 hours at 20°C

depth: 24 hours at 20 ° C

DRY

FEATURES & DURABILITY

It is a typically modern and elegant decorative watercolor for indoor use. NACRE can be applied to a wide range of surfaces. Thanks to its unique colors and shades, it can be used to create extremely contemporary and modern living spaces. The decorated surfaces highlight the beautiful and delicate, pearl and velvet finish shadows created by the different ways of application. The softness of the colors of NACRE decorative paint will transport you to a soothing and refreshing world.

ENVIRONMENTAL PERFORMANCE

PERFORMANCE	REGULATION	VALUE	TYPE
EMISSION OF INTERNAL POLLUTION SUBSTANCES TYPE R	ISO 16000	TVOC<1 Mg/mc3 CATEGORY A+	
WTO In the final product ready to use	REGULATION 2004-42-EC	Maximum 3g/L (EU maximum 200 g/L) Cat. Y/I	

SURFACE PREPARATION

Old wall. Remove all old, peeled and peeled paints and clean. Then apply a stabilizing primer depending on the type of surface. When the primer is completely dry, apply a coat of PRIMAIRE Avant Peinture-white PRIMER before painting and, after 4 hours at 20°C, proceed with the application of NACRE.

New wall. Clean (and if necessary, fill/putty) the surface you want to paint. Once dry, sand the surface and apply a coat of suitable primer. When the primer is completely dry, apply a coat of PRIMAIRE Avant Peinture-white PRIMER before painting and, after 4 hours at 20°C, proceed with the application of NACRE.

Dilution: Ready to use

PREPARATION OF THE PRODUCT

system with Roller, Spatula.

APPLICATION TOOLS

Layers: 2 layers

Mix well before application.

LAYERS

APPLICATION

1. **Roll & Spatula Application:** Apply one layer of NACRE with a short pile roll ($\pm 8\text{mm}$). Allow to dry ± 2 hours between layers.

Apply a 2nd layer of NACRE directly with a **Stainless Steel Spatula**, making moves in all directions to reveal the different finishes of the delicate pearl velvet finish.

2. **Roll and Wide Brush Application – PEARL EFFECT:** If you want to achieve the pearl pearl effect, add a package of **Perles de soie*** (silk pearls) to the NACRE container. Mix well and apply two thin coats with the wide brush in irregular cross-motions. Allow to dry ± 4 hours between layers.

**The addition of Perles de soie to the color does not affect the performance. Packaging: 200gr.*

NOTES:

The application temperature should be between $+5^{\circ}\text{C}$ and $+30^{\circ}\text{C}$. Wash the tools immediately after use with soap and water.

It can be kept for at least 2 years in its closed original packaging.