



PAILLETT'

TECHNICAL SPECIFICATIONS

NAME	PAILLETT'
TYPE	Decorative paint containing glitter powder.
USE	Water product for indoor use.
FEATURES	specific weight: 1.32 ± 30 gr/lit at 25 ° C Viscosity: = = = Yield: 7-8 m²/lit (may vary depending on roughness, surface absorbency and application method) Aesthetic result: matte with glitter flashes Colors: The colors from the catalog Packaging: LT. 2.0
DRY	surface: 2 hours at 20 ° C Repainting: 4 hours at 20°C depth: 24 hours at 20 ° C

FEATURES & DURABILITY

It is a typically modern and elegant decorative watercolor for indoor use. PAILLETT' can be applied to a wide range of surfaces. Thanks to its unique colors and shades, it can be used to create extremely contemporary and modern living spaces. The decorated surfaces highlight the precious metal fragments incorporated into the paint, enhancing the silver reflections from the glitter. PAILLETT' is a high-quality, breathable, washable and water-based product that can be repainted with any other water-based color.

ENVIRONMENTAL PERFORMANCE

PERFORMANCE	REGULATION	VALUE	TYPE
EMISSION OF INTERNAL POLLUTION SUBSTANCES TYPE R	ISO 16000	TVOC<1 Mg/mc3 CATEGORY A+	
WTO In the final product ready to use	REGULATION 2004-42-EC	Maximum 2g/L (EU maximum 200 g/L) Cat. Y/I	

SURFACE PREPARATION

Old wall. Remove all old, peeled and peeled paints and clean. Then apply a stabilizing primer depending on the type of surface. When the primer is completely dry, apply a coat of PRIMAIRE Avant Peinture-white PRIMER before painting and after 4 hours at 20°C, proceed with the application of PAILLETT'.

New wall. Clean (and if necessary, fill/putty) the surface you want to paint. Once dry, sand the surface and apply a coat of suitable primer. When the primer is completely dry, optionally apply a coat of PRIMAIRE Avant Peinture-white PRIMER before Painting and after 4 hours at 20°C, proceed with the application of PAILLETT'.

Dilution: Ready to use

PREPARATION OF THE PRODUCT

system with roller and brush

APPLICATION TOOLS

Layers: 2nd layer if required

LAYERS

APPLICATION

Apply PAILLETT' paint with the help of a roll with a medium pile ($\pm 8\text{mm}$). Switch in movements from left to right and top to bottom, and then finish by always working in the same direction and from top to bottom. Do not "drag" the paint in order to avoid creating marks. Allow to dry for ± 4 hours. Depending on the nature of your background and the color you choose, you may need to apply a second coat. You can remove stains (such as fingers, etc.) with a damp sponge.

NOTES:

The application temperature should be between $+5^{\circ}\text{C}$ and $+30^{\circ}\text{C}$. Wash the tools immediately after use with soap and water.

It can be kept for at least 2 years in its closed original packaging.